



NOTE:

1. LOCATIONS OF EXISTING UTILITIES MUST BE FIELD LOCATED WITH THEIR RESPECTIVE OWNERS BEFORE DIGGING OR MAKING NEW CONNECTIONS.
2. SANITARY SEWER CAN VARY 4' FROM CENTERLINE AROUND CURVES, HOWEVER DEQ MINIMUM SEPARATION DISTANCES MUST BE MET.
3. WATER AND SEWER LATERALS SHALL BE STUBBED OUT TO FAR SIDE OF THE UTILITY EASEMENT AND CLEARLY MARKED AS PER CITY STANDARD.
4. STREET LIGHTING SHALL BE AT EACH INTERSECTION AND MID-BLOCK WITH A MAXIMUM SPACING OF 350' BETWEEN LIGHT POLES.
5. UTILITY POLES, FIRE HYDRANTS, LIGHT POLES, AND STREET SIGNS SHALL BE LOCATED WITH 1.5' MINIMUM CLEARANCE FROM BACK OF CURB TO CLOSEST FACE OF UTILITY AND SHALL NOT BE PLACED INTO SIDEWALK UNLESS APPROVED BY CITY ENGINEER AND DRAWING NO. 1-2.
6. TRAFFIC CONTROL DEVICES AND THEIR LOCATION SHALL CONFORM TO LATEST ADOPTED EDITION OF MUTCD.
7. ALL UTILITY FRAME AND LIDS TO BE LOCATED OUTSIDE OF WHEEL PATHS AREAS. THE TOP OF THE UTILITIES WILL HAVE A TOLERANCE OF +0 TO -1/4".
8. TREE SPECIES AND PLACEMENT WITHIN RIGHT-OF-WAY MUST HAVE WRITTEN APPROVAL OF CITY FORESTER AND CITY ENGINEER.
9. ANY DEVIATION FROM THESE STANDARD SHALL HAVE WRITTEN CONSENT OF THE CITY ENGINEER.

CITY OF LEWISTON, IDAHO
PUBLIC WORKS DEPARTMENT

UTILITY LOCATIONS

APPROVED FOR PUBLICATION

Shawn J. Stalder 3/5/13
City Engineer Date

DWG. NO.

1-1