



NOTES:

1. 6' HIGH CHAIN LINK FENCE TO BE CONSTRUCTED OF GALVANIZED 9 GAUGE CORE WIRE WITH 2" MESH OR WALLS MAY BE CONSTRUCTED OF CONCRETE BLOCK OR BRICK.
2. PROVIDE CASTERS AND VERTICLE LOCKING DEVICES AT FREE ENDS OF DOORS.
3. DOORS MUST SWING OPEN AT LEAST 90 DEGREES FROM CLOSED POSITION.
4. DOORS MUST SWING FREELY AND BE ABLE TO BE LOCKED IN OPEN POSITION.
5. PROVIDE A MINIMUM OF 50 FEET "STRAIGHT-IN" APPROACH TO FRONT OF ENCLOSURE.
6. AREA MUST BE FREE OF OVERHEAD OBSTACLES, SUCH AS POWER LINES, BUILDING OVERHANGS, ETC.
7. CONTAINERS MUST BE PLACED ON A HARD LEVEL SURFACE, EITHER ASPHALT OR CONCRETE.
8. CONTAINER MUST BE COVERED.
9. FENCE POST TO BE SET IN CONCRETE TO A DEPTH OF 36" BELOW FINISHED GROUND LEVEL.
10. CONTACT SUNSHINE DISPOSAL FOR APPROPRIATE SIZE OF CONTAINERS.

CITY OF LEWISTON, IDAHO
PUBLIC WORKS DEPARTMENT

**10' x 10'
REFUSE CONTAINER
STORAGE AREA**

APPROVED FOR PUBLICATION

Deann Stetler 10/21/10
City Engineer Date

DWG. NO.

7-2